

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

Tulajdonságok

Üzemi nyomás	0 - 35 bar
Levegő átláramlás	2.100 l/min (at $\Delta p = 0.5$ bar)
Közeghőmérséklet	-20 °C to +40 °C
Menetes idom	Nickel-plated brass
Szeleptest	Steel, QPQ treated
Oldóhüvely	Extremely robust, ergonomic plastic
Szelep, ülék	Brass
Közegek	Only for clean compressed air
Tömítéstechnika	NBR
Rugók, biztosítógyűrű, golyók	stain less steel



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Cikk

Megnevezés	Csatlakozás	Hossz (mm)	SW (mm)
K- 07 35 08 47	G 1/4 male	65,0	19
K- 07 35 08 48	G 3/8 male	65,0	19
K- 07 35 08 49	G 1/2 male	59,0	22

kiegészítő elemek

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass