

K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continous thread

HANSA FLEX

Tulajdonságok

Munkanyomás	Max. 50 bar
Csatlakozómenet	acc. ISO 7-1
Anyag	black steel ST 37-2



Megjegyzés

További adatokért vegye fel a kapcsolatot.

Leírás

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

Cikk

Megnevezés	Menet	Hossz (mm)
K- 07 40 35 30	R 1/4	25,0
K- 07 40 35 33	R 3/8	26,0
K- 07 40 35 29	R 1/2	34,0
K- 07 40 35 32	R 3/4	36,0
K- 07 40 35 26	R 1	43,0
K- 07 40 35 28	R 1 1/4	48,0
K- 07 40 35 27	R 1 1/2	48,0
K- 07 40 35 31	R 2	56,0
K- 07 40 50 36	R 2 1/2	65,0
K- 07 40 50 37	R 3	71,0