


K-LKM S NW7,4 DREH AG VA

Safety couplings DN 7.4, stainless steel 1.4404, male, swivel type

HANSA FLEX

Tulajdonságok

Üzemi nyomás	max. 10 bar
Levegő átáramlás	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Közeghőmérséklet	-20 °C to +150 °C
ház	Stainless steel 1.4404
Menet	Stainless steel 1.4404
Belső alkatrészek	Stainless steel 1.4404
Gomb, szelep	Stainless steel 1.4404
Tömítő anyag	FKM



Megjegyzés

Not suitable for hitting / pulsating tools.

További adatokért vegye fel a kapcsolatot.

Leírás

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

További információk

Not suitable for hitting / pulsating tools.

Cikk

Megnevezés	Csatlakozás	Hossz (mm)	SW (mm)
K- 07 35 12 76	G 1/4 male	70,5	21
K- 07 35 12 77	G 3/8 male	70,0	21
K- 07 35 12 78	G 1/2 male	72,5	25