

# K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass

**HANSA FLEX**

## Tulajdonságok

Csatlakozási mód connection nipples and coupling NW 7,2

Üzemi hőmérséklet -40 °C to +74 °C



## Megjegyzés

További adatokért vegye fel a kapcsolatot.

## Leírás

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

## Cikk

Megnevezés	Ø tömlő belül (mm)	Ø tömlő kívül (mm)	Ø Külső tekerecs (mm)	Max. working pressure resistance at 23°C (bar)	max. munkahossz (m)
K- 07 10 12 72	5,0	8,0	40	10	3,0
K- 07 10 12 74	5,0	8,0	40	10	6,0
K- 07 10 12 76	5,0	8,0	40	10	7,5
K- 07 10 12 81	6,3	9,5	60	10	3,0
K- 07 10 12 83	6,3	9,5	60	10	6,0
K- 07 10 12 85	6,3	9,5	60	10	7,5
K- 07 10 12 79	6,3	9,5	60	10	10,0
K- 07 10 12 90	8,0	12,0	80	9	3,0
K- 07 10 12 92	8,0	12,0	80	9	6,0
K- 07 10 12 94	8,0	12,0	80	9	7,5
K- 07 10 12 88	8,0	12,0	80	9	10,0

## Tartozék

K-DREHBARE VERSCHRAUBUNG Swivel adapters