

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Tulajdonságok

max. üzemi nyomás	0,7 MPa
min. üzemi nyomás	0.10 MPa
Kivitel	rack and pinion
Közeghőmérséklet	0 °C to +60 °C
Környezeti hőmérséklet	0 °C to +60 °C
Fordítási szög	0 to 190°
Közegek	Sűrített levegő
Sorozat	MSQ
További információk	narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table \nAir connections of 2 pages possible



Cikk

Megnevezés	Ø Dugattyú (mm)	Pneumatikus csatlakozó	Méret	Csillapítás	Tömeg/méter (kg)
K- 07 55 01 13	6	M 3	1	without, with adjustment bolt	0,075
K- 07 55 01 18	8	M 5	2	without, with adjustment bolt	0,105
K- 07 55 01 21	10	M 5	3	elastic, with adjustment bolt	0,150
K- 07 55 01 26	12	M 5	7	elastic, with adjustment bolt	0,250
K- 07 55 01 11	15	M 5	10	elastic, with adjustment bolt	0,530
K- 07 55 01 16	18	M 5	20	elastic, with adjustment bolt	0,990
K- 07 55 01 19	21	G 1/8	30	elastic, with adjustment bolt	1,290
K- 07 55 01 22	25	G 1/8	50	elastic, with adjustment bolt	2,080
K- 07 55 01 24	28	G 1/8	70	elastic, with adjustment bolt	2,880
K- 07 55 01 09	32	G 1/8	100	elastic, with adjustment bolt	4,090
K- 07 55 01 14	40	G 1/8	200	elastic, with adjustment bolt	7,580
K- 07 55 01 12	15	M 5	10	elastic, with integrated shock absorber	0,540
K- 07 55 01 17	18	M 5	20	elastic, with integrated shock absorber	0,990
K- 07 55 01 20	21	G 1/8	30	elastic, with integrated shock absorber	1,290
K- 07 55 01 23	25	G 1/8	50	elastic, with integrated shock absorber	2,100
K- 07 55 01 25	28	G 1/8	70	elastic, with integrated shock absorber	2,880
K- 07 55 01 10	32	G 1/8	100	elastic, with integrated shock absorber	4,100
K- 07 55 01 15	40	G 1/8	200	elastic, with integrated shock absorber	7,650