

K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA FLEX

Tulajdonságok

| | |
|------------------------|--|
| max. üzemi nyomás | 0,7 MPa |
| min. üzemi nyomás | 0.10 MPa |
| Kivitel | rack and pinion |
| Közeghőmérséklet | 0 °C to +60 °C |
| Környezeti hőmérséklet | 0 °C to +60 °C |
| Fordítási szög | 0 to 190° |
| Közegek | Sűrített levegő |
| Sorozat | MSQ |
| További információk | narrow pivot table unit with low overall height the rotation angle can be adjusted continuously Positioning the housing allow for quick installation the load can be mounted directly on the pivot table \nAir connections of 2 pages possible |



Cikk

| Megnevezés | Ø Dugattyú (mm) | Pneumatikus csatlakozó | Méret | Csillapítás | Tömeg/méter (kg) |
|----------------|-----------------|------------------------|-------|---|------------------|
| K- 07 55 01 13 | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| K- 07 55 01 18 | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| K- 07 55 01 21 | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| K- 07 55 01 26 | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| K- 07 55 01 11 | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| K- 07 55 01 16 | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| K- 07 55 01 19 | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| K- 07 55 01 22 | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| K- 07 55 01 24 | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| K- 07 55 01 09 | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| K- 07 55 01 14 | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| K- 07 55 01 12 | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| K- 07 55 01 17 | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| K- 07 55 01 20 | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| K- 07 55 01 23 | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| K- 07 55 01 25 | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| K- 07 55 01 10 | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| K- 07 55 01 15 | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |