# LKM MM ST DK

Dugós csatlakozó - karmantyú (levegő) biztosítással

## Tulajdonságok

| | |
|---|---|
| **Szerkezeti mód** | Gyorszár csatlakozó-hüvely |
| **Csatlakozás 1** | Tömlőcsatlakozás |
| **Csatlakozás 2** | |
| **Üzemi nyomás** | max. 12 bar |
| **Levegő átáramlás** | 1.800 l/min (at 6 bar and Δp = 1 bar) |
| **Közeghőmérséklet** | -20 °C to +70 °C |
| **ház** | Aluminium, anodised |
| **Menet** | Nickel-plated brass |
| **Belső alkatrészek** | Stainless steel |
| **Gomb, szelep** | Hardened, galvanised steel |
| **Tömítő anyag** | NBR |



## Megjegyzés

Not suitable for hitting / pulsating tools.
További adatokért vegye fel a kapcsolatot.

## Leírás

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

## Cikk

| Megnevezés | tömlő belső átmérőhöz (mm) | Csatlakozás | Hossz (mm) | SW (mm) |
|---|---|---|---|---|
| **LKM 06 MM ST DK** | 6 | Stem, I.D. 6 | 88,5 | 21 |
| **LKM 09 MM ST DK** | 9 | Stem, I.D. 9 | 88,5 | 21 |
| **LKM 13 MM ST DK** | 13 | Stem, I.D. 13 | 88,5 | 21 |