


Caratteristiche				
Tipo	per fermatubo semplice			
Serie	pesante			
Norma	DIN 3015-2			
Materiale	Acciaio			
Protezione superficiale	Size 1 to size 4 electro galvanised uncoated from size 5			





Dimensione fascetta	a1	a2	B (mm)	L (mm)	S (mm)
1	14,0	15,5	30	55	8
2	26,0	15,5	30	70	8
3	41,0	15,5	30	85	8
4	69,0	17,5	45	115	10
5	97,0	21,5	60	152	10
6	137,0	27,5	80	205	15
7	169,0	30,5	90	250	15
8	219,0	36,5	120	320	25
	1 2 3 4 5 6 7	(mm) 1 14,0 2 26,0 3 41,0 4 69,0 5 97,0 6 137,0 7 169,0	(mm) (mm) 1 14,0 15,5 2 26,0 15,5 3 41,0 15,5 4 69,0 17,5 5 97,0 21,5 6 137,0 27,5 7 169,0 30,5	(mm) (mm) (mm) 1 14,0 15,5 30 2 26,0 15,5 30 3 41,0 15,5 30 4 69,0 17,5 45 5 97,0 21,5 60 6 137,0 27,5 80 7 169,0 30,5 90	(mm) (mm) (mm) (mm) 1 14,0 15,5 30 55 2 26,0 15,5 30 70 3 41,0 15,5 30 85 4 69,0 17,5 45 115 5 97,0 21,5 60 152 6 137,0 27,5 80 205 7 169,0 30,5 90 250

Varianti dei prodotti

SRS SIP V4 Piastra di sicurezza per fermatubo semplice, Acciaio inossidabile 1.4571

è un elemento supplementare dei seguenti prodotti

C A Assemblaggio del gruppo C