

HK CFVP

Fondo del cilindro con scarico dell'olio

HANSA FLEX

Caratteristiche

Materiale Acciaio S355J0 (Fe510C)



Articolo

| Denominazione | Ø AL (mm) | Ø T (mm) | G | L (mm) | LF (mm) | S (mm) | S1 (mm) | Peso (kg) |
|--------------------|--------------|-------------|--------|-----------|------------|-----------|------------|--------------|
| HK CFVP 040 050 04 | 40 | 50 | G 1/4" | 17,0 | 30 | 40 | 2 | 0,54 |
| HK CFVP 050 060 06 | 50 | 60 | G 3/8" | 17,0 | 35 | 40 | 2 | 0,77 |
| HK CFVP 060 070 06 | 60 | 70 | G 3/8" | 17,0 | 35 | 40 | 2 | 1,10 |
| HK CFVP 063 073 06 | 63 | 73 | G 3/8" | 17,0 | 35 | 40 | 2 | 1,17 |
| HK CFVP 070 080 06 | 70 | 80 | G 3/8" | 17,0 | 35 | 40 | 2 | 1,41 |
| HK CFVP 080 095 08 | 80 | 95 | G 1/2" | 20,0 | 45 | 50 | 2 | 2,49 |
| HK CFVP 090 105 08 | 90 | 105 | G 1/2" | 20,0 | 45 | 50 | 2 | 3,11 |
| HK CFVP 100 115 08 | 100 | 115 | G 1/2" | 20,0 | 45 | 50 | 2 | 3,70 |