

| Caratteristiche | | | |
|-------------------------|----------------|--|--|
| Attacco 1 | Giunto maschio | | |
| Materiale | Acciaio | | |
| Protezione superficiale | nero | | |



| Articolo | | | |
|------------------|-----------------------|-------------------|-------------------|
| Denominazione | Pressione d'esercizio | Misura del giunto | per flessibili DI |
| PRT S 50 DN 50 | (bar) | (mm) 50,0 | (mm) 50 |
| | 12,0 | • | |
| PRT S 70 DN 63 | 12,0 | 70,0 | 63 |
| PRT S 70 DN 70 | 12,0 | 70,0 | 70 |
| PRT S 70 DN 75 | 12,0 | 70,0 | 75 |
| PRT S 89 DN 75 | 12,0 | 89,0 | 75 |
| PRT S 89 DN 80 | 12,0 | 89,0 | 80 |
| PRT S 89 DN 89 | 12,0 | 89,0 | 89 |
| PRT S 108 DN 75 | 12,0 | 108,0 | 75 |
| PRT S 108 DN 90 | 12,0 | 108,0 | 90 |
| PRT S 108 DN 102 | 12,0 | 108,0 | 102 |
| PRT S 108 DN 110 | 12,0 | 108,0 | 110 |
| PRT S 108 DN 152 | 12,0 | 108,0 | 152 |
| PRT S 108 DN 127 | 12,0 | 108,0 | 127 |
| PRT S 133 DN 50 | 12,0 | 133,0 | 50 |
| PRT S 133 DN 76 | 12,0 | 133,0 | 76 |
| PRT S 133 DN 102 | 12,0 | 133,0 | 102 |
| PRT S 133 DN 110 | 12,0 | 133,0 | 110 |
| PRT S 133 DN 127 | 12,0 | 133,0 | 127 |
| PRT S 133 DN 133 | 12,0 | 133,0 | 133 |
| PRT S 133 DN 152 | 12,0 | 133,0 | 152 |
| PRT S 159 DN 50 | 12,0 | 159,0 | 50 |
| PRT S 159 DN 76 | 12,0 | 159,0 | 76 |
| PRT S 159 DN 102 | 12,0 | 159,0 | 102 |
| PRT S 159 DN 127 | 12,0 | 159,0 | 127 |
| PRT S 159 DN 133 | 12,0 | 159,0 | 133 |
| PRT S 159 DN 152 | 12,0 | 159,0 | 152 |
| PRT S 159 DN 159 | 12,0 | 159,0 | 159 |
| PRT S 216 DN 200 | 12,0 | 216,0 | 200 |
| | | | |