

K-MANO

Pressure gauges (CrNi steel type / connection on rear)

HANSA FLEX

Caratteristiche

Tipo	232.50
Esecuzione	Bourdon-tube pressure gauge, CrNi steel type, all-stainless steel
Applicazione	For gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Classe di qualità	1,6 (Ø 63 mm), 1,0 (Ø 100 mm)
Temperatura del fluido	max. +200 °C
Temperatura ambiente	-40 °C to +60 °C
Alloggiamento	CrNi steel
Oculare	Laminated safety glass Ø 63 = Polycarbonate



Nota

Altri dati su richiesta.

Articolo

Denominazione	Campo di misurazione	Ø (mm)	Attacco
K- 07 20 06 10	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 06 11	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 06 12	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 06 13	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 06 14	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 06 15	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 06 16	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 06 17	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 06 18	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 06 19	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 00 53	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 00 54	0 - 10.0 bar	100,0	G 1/2"