

K-MANO ABSPH ZAPF DREH MUF2

Pressure gauge stopcocks, male - loose (rotatable) female

Caratteristiche

Applicazione	For all pressure gauges with a flat gasket acc. to DIN 16258
Intervallo di pressione	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
Temperatura	Max. +50 °C
Alloggiamento	Brass with a bare metal surface or stainless steel 1.4571
Impugnatura	Plastic
Flangia per prove	-



Nota

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B
K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Altri dati su richiesta.

Descrizione

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

Informazioni supplementari

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

Articolo

Denominazione	Filetto	PN (bar)	SW (mm)	Materiale
K- 07 20 11 17	G 1/2	25	27	Ottone
K- 07 20 11 18	G 1/2	25	27	Ottone