# K-MANO ABSPH ZAPF SPAN MUF

Pressure gauge stopcocks, male - female/female

## Caratteristiche

| | |
|---|---|
| **Applicazione** | For all pressure gauges with a flat gasket acc. to DIN 16258 |
| **Intervallo di pressione** | Max. 16 bar, depending on the variantPressure gauge valves should be used for higher pressures |
| **Temperatura** | Max. +50 °C |
| **Alloggiamento** | Brass with a bare metal surface or stainless steel 1.4571 |
| **Impugnatura** | Plastic |
| **Flangia per prove** | - |



## Nota

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B
Altri dati su richiesta.

## Descrizione

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Informazioni supplementari

Further measuring ranges on request
Version for panel mounting available on request. Version with max. pointer available on request

## Articolo

| Denominazione | Filetto | PN (bar) | SW (mm) | Materiale |
|---|---|---|---|---|
| **K- 07 20 11 27** | G 1/4 | 6 | 17 | Ottone |
| **K- 07 20 11 29** | G 1/2 | 25 | 27 | Ottone |
| **K- 07 20 11 28** | G 1/2 | 25 | 27 | Stainless steel |
| **K- 07 20 11 31** | G 1/2 | 25 | 27 | Ottone |
| **K- 07 20 11 30** | G 1/2 | 25 | 27 | Stainless steel |
| **K- 07 20 11 32** | G 1/2 | 25 | 27 | Ottone |

*Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.*