

# K-MANO ABSPH ZAPF SPAN MUF

Pressure gauge stopcocks, male - female/female

**HANSA FLEX**

## Caratteristiche

<b>Applicazione</b>	For all pressure gauges with a flat gasket acc. to DIN 16258
<b>Intervallo di pressione</b>	Max. 16 bar, depending on the variant Pressure gauge valves should be used for higher pressures
<b>Temperatura</b>	Max. +50 °C
<b>Alloggiamento</b>	Brass with a bare metal surface or stainless steel 1.4571
<b>Impugnatura</b>	Plastic
<b>Flangia per prove</b>	-



## Nota

K-07201090, K-07201091 in acc. with DIN 16261-A, K-07201096, K-07201097 in acc. with DIN 16261-B <br>K-07201128, K-07201129 in acc. with DIN 16262-A, K-07201127 in acc. with DIN 16262-B  
Altri dati su richiesta.

## Descrizione

It is useful to install a stopcock as a shut-off element between the pressure gauge and the pipe. When the lever is set to the »blow out« position, the medium is discharged into the atmosphere. Stopcocks with a test port allow pressure gauges to be simultaneously connected to the pipe.

## Informazioni supplementari

Further measuring ranges on request

Version for panel mounting available on request. Version with max. pointer available on request

## Articolo

Denominazione	Filetto	PN (bar)	SW (mm)	Materiale
K- 07 20 11 27	G 1/4	6	17	Ottone
K- 07 20 11 29	G 1/2	25	27	Ottone
K- 07 20 11 28	G 1/2	25	27	Stainless steel
K- 07 20 11 31	G 1/2	25	27	Ottone
K- 07 20 11 30	G 1/2	25	27	Stainless steel
K- 07 20 11 32	G 1/2	25	27	Ottone