

# K-RMM HFR STAHLBLECH CR

Standard pressure gauges with chrome-plated sheet-steel bezel, connection on rear

**HANSA FLEX**

## Caratteristiche

<b>Tipo</b>	111.12
<b>Esecuzione</b>	Bourdon-tube pressure gauge, standard design, mounting ring
<b>Applicazione</b>	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
<b>Classe di qualità</b>	1,6
<b>Temperatura del fluido</b>	max. +60 °C
<b>Temperatura ambiente</b>	da -20 °C a +60 °C
<b>Alloggiamento</b>	Sheet steel
<b>Materiale organo di misura e minuteria</b>	Lega di rame
<b>Oculare</b>	Transparent plastic



## Nota

Altri dati su richiesta.

## Articolo

Denominazione	Campo di misurazione	Ø (mm)	Attacco
K- 07 20 04 37	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 38	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 39	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 40	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 41	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 42	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 43	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 44	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 45	0 - 25.0 bar	40,0	G 1/8
K- 07 20 04 46	0 - 40.0 bar	40,0	G 1/8
K- 07 20 05 41	-1 / 0.0 bar	50,0	G 1/4
K- 07 20 05 42	0 - 1.0 bar	50,0	G 1/4
K- 07 20 05 43	0 - 1.6 bar	50,0	G 1/4
K- 07 20 05 44	0 - 2.5 bar	50,0	G 1/4
K- 07 20 05 45	0 - 4.0 bar	50,0	G 1/4
K- 07 20 05 46	0 - 6.0 bar	50,0	G 1/4
K- 07 20 05 47	0 - 10.0 bar	50,0	G 1/4
K- 07 20 05 48	0 - 16.0 bar	50,0	G 1/4
K- 07 20 05 49	0 - 25.0 bar	50,0	G 1/4
K- 07 20 05 50	0 - 40.0 bar	50,0	G 1/4