

K-RMM HKR STAHL

Standard pressure gauges with 3-hole bezel, chrome-plated steel, dual scale in bar/psi and clamp fixing, connection on rear

HANSA FLEX

Caratteristiche

Tipo	111.12
Esecuzione	Bourdon-tube pressure gauge, standard design, mounting ring Chromium plated sheet steel Steel chrome plated or black or with triangular bezel
Applicazione	gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise
Classe di qualità	2,5
Temperatura del fluido	max. +60 °C
Temperatura ambiente	da -20 °C a +60 °C
Alloggiamento	Sheet steel
Materiale organo di misura e minuteria	Lega di rame
Oculare	Transparent plastic



Nota

Altri dati su richiesta.

Articolo

Denominazione	Campo di misurazione	Ø (mm)	Attacco
K- 07 20 04 04	-1 / 0.0 bar	40,0	G 1/8
K- 07 20 04 05	0 - 1.0 bar	40,0	G 1/8
K- 07 20 04 06	0 - 1.6 bar	40,0	G 1/8
K- 07 20 04 07	0 - 2.5 bar	40,0	G 1/8
K- 07 20 04 08	0 - 4.0 bar	40,0	G 1/8
K- 07 20 04 09	0 - 6.0 bar	40,0	G 1/8
K- 07 20 04 10	0 - 10.0 bar	40,0	G 1/8
K- 07 20 04 11	0 - 16.0 bar	40,0	G 1/8
K- 07 20 04 12	0 - 25.0 bar	40,0	G 1/8