

K-TR PA 612

Plastic pipes made of polyamide PA 12 (10 pcs.)

HANSA FLEX

Caratteristiche

Temperatura d'esercizio	-60 °C to +100 °C (PA 12)
Caratteristiche	Resistant to corrosion, vibration, impact, ageing, high pressures and heat
Lunghezza tubo	3 m
Confezione:	10 lengths (O.D. 28 mm in packs of 5 lengths), only sold in complete packaging units!
Materiale	Polyamid PA 12, hard (according to DIN 73378)



Nota

Operating pressure with 2.5 x overpressure safety!
Altri dati su richiesta.

Descrizione

Push-in fittings - aluminium pipes - plastic pipes - take-off points. The flexible, maintenance-free compressed air installation system from compressor to take-off point. For Ø 12 mm to Ø 32 mm pipe systems and for Ø 4 mm to Ø 12 mm pneumatic applications

Articolo

Denominazione	diametro esterno del tubo Ø (mm)	Ø interno del tubo (mm)	pressione d'esercizio max. a 20°C (bar)	Colore
K- 07 10 04 57	12	9	38	blu
K- 07 10 04 59	12	9	38	nero
K- 07 10 04 61	15	12	25	blu
K- 07 10 04 63	15	12	25	nero
K- 07 10 04 65	18	14	28	blu
K- 07 10 04 67	18	14	28	nero
K- 07 10 04 69	22	18	22	blu
K- 07 10 04 71	22	18	22	nero
K- 07 10 04 73	28	23	20	blu
K- 07 10 04 75	28	23	20	nero