
K-LKM 5 UWB

Non-interchangeable quick disconnect couplings DN 5

Caratteristiche

Pressione d'esercizio	0 - 35 bar, maximum static working pressure (non-pulsating)
Portata aria	560 l/min (at 6 bar and Δp = 0.5 bar)
Temperatura del fluido	-20 °C to +100 °C
Bussola di sblocco	Anodised aluminium
Molla, anello elastico, sfere	stain less steel
Materiale di tenuta	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Altri dati su richiesta.

Descrizione

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Articolo

Denominazione	Attacco	Colore	Lunghezza (mm)	SW (mm)
K- 07 35 06 80	G 1/8 male	verde	45,0	14
K- 07 35 06 81	G 1/4 male	verde	47,0	17
K- 07 35 06 82	G 1/8 female	verde	45,0	14
K- 07 35 06 83	G 1/4 female	verde	47,0	17
K- 07 35 06 84	G 1/8 male	Brown	45,0	14
K- 07 35 06 85	G 1/4 male	Brown	47,0	17
K- 07 35 06 86	G 1/8 female	Brown	45,0	14
K- 07 35 06 87	G 1/4 female	Brown	47,0	17
K- 07 35 06 88	G 1/8 male	blu	45,0	14
K- 07 35 06 89	G 1/4 male	blu	47,0	17
K- 07 35 06 90	G 1/8 female	blu	45,0	14
K- 07 35 06 91	G 1/4 female	blu	47,0	17
K- 07 35 06 92	G 1/8 male	rosso	45,0	14
K- 07 35 06 93	G 1/4 male	rosso	47,0	17
K- 07 35 06 94	G 1/8 female	rosso	45,0	14
K- 07 35 06 95	G 1/4 female	rosso	47,0	17

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.