

K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

HANSA FLEX

Caratteristiche

Pressione d'esercizio	0 - 35 bar, maximum static working pressure (non-pulsating)
Portata aria	1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Temperatura del fluido	-20 °C to +100 °C
Alloggiamento	Brass
Valvola	Die-cast zinc, nickel-plated
Bussola di sblocco	Anodised aluminium
Molla, anello elastico, sfere	stain less steel
Materiale di tenuta	NBR



Nota

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.

Altri dati su richiesta.

Descrizione

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Articolo

Denominazione	Attacco	Colore	Lunghezza (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	verde	57,5	19
K- 07 35 08 02	G 3/8 male	verde	57,5	19
K- 07 35 08 03	G 1/4 female	verde	55,5	19
K- 07 35 08 04	G 3/8 female	verde	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	blu	57,5	19
K- 07 35 08 10	G 3/8 male	blu	57,5	19
K- 07 35 08 11	G 1/4 female	blu	55,5	19
K- 07 35 08 12	G 3/8 female	blu	54,5	19
K- 07 35 08 13	G 1/4 male	rosso	57,5	19
K- 07 35 08 14	G 3/8 male	rosso	57,5	19
K- 07 35 08 15	G 1/4 female	rosso	55,5	19
K- 07 35 08 16	G 3/8 female	rosso	54,5	19