

K-INLINE-EJEKTTOREN SLP

Inline ejectors »SLP«, plug connection

HANSA FLEX

Caratteristiche

Caratteristiche Vacuum generator with high maximum vacuum level (85% vacuum)
No moving parts, which means no wear and no maintenance
ultra small footprint, suitable for confined spaces
minimal air consumption
low noise

Applicazione by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces

Alloggiamento plastic (Typ SLP)

Sistema ugello Brass (type VR)

Attacco thread connector



Nota

Altri dati su richiesta.

Descrizione

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Articolo

Denominazione	Dimensione ugello	Attacco aria di scarico	Attacco aria compressa	Attacco per vuoto	Grado di evacuazione	Consumo d'aria aspirazione (L/min)	capacità di aspirazione max. (L/min)	Lungh-ezza (mm)	Pressione d'esercizio (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5