

K-SAUGPLATTENAUFHAENGUNG

Flexible suction pad mountings

Caratteristiche

Applicazione	For handling of workpieces with sloping using large-area vacuum gripper Handling of large plates that can sag when lifting In combination with spring plungers to compensate height-differences and Uneveness
Caratteristiche particolari	very good adaptation to oblique workpiece surfaces automatic Rückstellung in die Ausgangslage vacuum-tight design with integrated protection against damage





Nota

Altri dati su richiesta.

Descrizione

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

Articolo

Denominazione	Filettatura 1 interna	Filettatura 2 esterna	H (mm)	Materiale	L1 (mm)	L2 (mm)	Angolo W (°)	Carico verticale (N/m2)	Momento di flessione (N/m2)	SW (mm)
K- 07 45 01 47	G 1/4	M 10 x 1.25	27,0	Steel, rubber	10,5	8,0	12	500	8,0	17
K- 07 45 01 48	G 1/4	G 1/4	27,0	Steel, rubber	12,0	12,0	12	750	10,0	17

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.