

# K-DRS MDR 5 O ENTLASTU VENT

»MDR 5« pressure switches, without unloading valve / on/off switch / motor protection circuit, with flange 1/4

**HANSA FLEX**

## Caratteristiche

Temperatura del fluido	-5 °C to +80 °C
pressione d'arresto max.	16 bar
Capacità di commutazione	5,5 kW
Tipo di contatto	NC (3-pole)
frequenza di commutazione max.	120 (electrical), 600 (mechanical)
Grado di protezione	IP 54



## Nota

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)  
Altri dati su richiesta.

## Descrizione

Three-phase version

## Avvertenza per l'ordinazione

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

## Informazioni supplementari

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

## Articolo

Denominazione	Attacco aria compressa	Intervallo di regolazione
K- 07 30 24 24	G 1/2	2,0 - 11,0 bar
K- 07 30 24 26	G 1/2	2,5 - 16,0 bar