

K-3 BKR T DOPPELWIRKEND T1

Stainless steel ball valves, 3-way, with double-acting actuator, T-bore, normal position T1

HANSA FLEX

Caratteristiche

| | |
|--------------------------------------|--|
| Tipo | Pneumatic actuators, in double- or single acting version, with integrated end-position feedback |
| Foro | Forma a T |
| Pressione d'esercizio | max. 63 bar (depending on temperature and nominal size) |
| Temperatura d'esercizio | -20 °C to +70 °C |
| Angolo di rotazione | 90 ° |
| Interfacce standardizzate | Interface actuator / valve: four or eight threaded holes in the drive housing according to EN ISO 5211, Interface actuator / S |
| Pressione di comando | 5.5 bar |
| Adattatore valvola | Acc. to NAMUR |
| Azionamento | aluminium eloxed |
| Guarnizione azionamento | NBR |
| Rubinetto a sfera | Stainless steel 1.4401, with ISO-flange plate |
| Guarnizione rubinetto a sfera | PTFE/FKM |



Nota

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Altri dati su richiesta.

Descrizione

3-way cock, reduced bore

Informazioni supplementari

Other T-positions on request

Articolo

| Denominazione | DN | Filetto | Posizione | A (mm) | B (mm) | D (mm) | L (mm) | SW (mm) |
|----------------|----|----------|-----------|-----------|-----------|-----------|-----------|------------|
| K- 07 30 02 99 | 15 | Rp 1/2 | T 1 | 116,0 | 130,0 | 20,0 | 73,0 | 27 |
| K- 07 30 03 01 | 20 | Rp 3/4 | T 1 | 116,0 | 136,0 | 23,0 | 80,0 | 32 |
| K- 07 30 03 03 | 25 | Rp 1 | T 1 | 133,0 | 148,5 | 28,5 | 90,0 | 41 |
| K- 07 30 03 05 | 32 | Rp 1 1/4 | T 1 | 133,0 | 153,5 | 36,5 | 90,0 | 50 |
| K- 07 30 03 07 | 40 | Rp 1 1/2 | T 1 | 137,0 | 173,0 | 37,0 | 105,0 | 55 |
| K- 07 30 03 09 | 50 | Rp 2 | T 1 | 161,0 | 196,5 | 47,5 | 115,0 | 71 |