
## K-RD SCHRAEGSITZ MS

Unidirectional valves



Caratteristiche	
Pressione d'esercizio	max. 10 bar
Filettatura descrizione	Rp thread acc. to DIN 2999
Temperatura del fluido	max. +80 °C
Pressione di apertura	min. 0.5 bar
Temperatura ambiente	Max. +80 °C
Materiale di tenuta	NBR
Alloggiamento	Brass





## Nota

Altri dati su richiesta.

Filetto	B (mm)	L (mm)	SW (mm)	
Rp 3/8	50,0	55,0	27	
Rp 1/2	50,0	59,0	27	
Rp 3/4	60,0	67,0	32	
Rp 1	71,0	83,0	38	
Rp 1 1/4	97,0	96,0	48	
Rp 1 1/2	114,0	106,0	54	
Rp 2	135,0	130,0	68	
	Rp 3/8 Rp 1/2 Rp 3/4 Rp 1 Rp 1 Rp 1 1/4 Rp 1 1/2	Rp 3/8 50,0 Rp 1/2 50,0 Rp 3/4 60,0 Rp 1 71,0 Rp 1 1/4 97,0 Rp 1 1/2 114,0	(mm)         (mm)           Rp 3/8         50,0         55,0           Rp 1/2         50,0         59,0           Rp 3/4         60,0         67,0           Rp 1         71,0         83,0           Rp 1 1/4         97,0         96,0           Rp 1 1/2         114,0         106,0	(mm)         (mm)         (mm)           Rp 3/8         50,0         55,0         27           Rp 1/2         50,0         59,0         27           Rp 3/4         60,0         67,0         32           Rp 1         71,0         83,0         38           Rp 1 1/4         97,0         96,0         48           Rp 1 1/2         114,0         106,0         54