

# K-SPV DOPPEL

## Check valves, double-acting

### Caratteristiche

<b>Pressione d'esercizio</b>	max. 10 bar
<b>Pressione di comando</b>	min. 3.0 bar, max. 8 bar with double-acting actuator; min. 4.2 bar, max. 8 bar for single-drive
<b>Temperatura</b>	-20 °C to +80 °C (NBR); -20 °C to +150 °C (FKM)
<b>Attacco</b>	NAMUR-Interface, direct: 2 x G 1/8
<b>Inserzione</b>	Any
<b>Alloggiamento, parti interne</b>	Nickel-plated brass
<b>Molla</b>	Stainless-steel
<b>Materiale di tenuta</b>	Perbunan (NBR) or FKM (FPM)



### Nota

Altri dati su richiesta.

### Descrizione

2/2-way check valves, specially designed for automated industrial plant engineering. A low-price, compact, space-saving and reliable alternative to ball valves with a pneumatic rotary actuator. <br>These valves have a full bore.

### Articolo

Denominazione	DN	Filetto	Materiale di tenuta	H (mm)	L (mm)
K- 07 30 25 37	10	Rp 3/8	NBR	46,0	98,0
K- 07 30 25 38	15	Rp 1/2	NBR	51,7	112,0
K- 07 30 25 39	20	Rp 3/4	NBR	63,5	135,0
K- 07 30 25 40	25	Rp 1	NBR	69,0	143,0
K- 07 30 25 41	10	Rp 3/8	FKM	46,0	98,0
K- 07 30 25 42	15	Rp 1/2	FKM	51,7	112,0
K- 07 30 25 43	20	Rp 3/4	FKM	63,5	135,0
K- 07 30 25 44	25	Rp 1	FKM	69,0	143,0