


K-XVMK 6

Male connectors, conical male thread acc. to ISO 7-1

HANSA FLEX

Caratteristiche

| | |
|-------------------------|------------------|
| Intervallo di pressione | Max. 60 bar |
| Temperatura | Max. 150 °C |
| Materiale | Ottone nichelato |



Nota

Altri dati su richiesta.

Articolo

| Denominazione | Ø esterno del tubo | Filetto | L1 (mm) | SW | SW1 (mm) |
|----------------|--------------------|---------|------------|-------|-------------|
| K- 07 40 20 02 | 4 mm | R 1/8 | 27,0 | 10 mm | 10 |
| K- 07 40 20 03 | 6 mm | R 1/8 | 28,0 | 12 mm | 12 |
| K- 07 40 20 04 | 8 mm | R 1/8 | 29,5 | 12 mm | 14 |
| K- 07 40 20 05 | 6 mm | R 1/4 | 32,5 | 14 mm | 12 |
| K- 07 40 20 06 | 8 mm | R 1/4 | 33,0 | 14 mm | 14 |
| K- 07 40 20 07 | 10 mm | R 1/4 | 37,5 | 17 mm | 19 |
| K- 07 40 20 08 | 8 mm | R 3/8 | 33,0 | 17 mm | 14 |
| K- 07 40 20 09 | 10 mm | R 3/8 | 38,0 | 17 mm | 19 |
| K- 07 40 20 13 | 12 mm | R 3/8 | 39,0 | 19 mm | 22 |
| K- 07 40 20 18 | 10 mm | R 1/2 | 40,5 | 22 mm | 19 |
| K- 07 40 20 19 | 12 mm | R 1/2 | 41,0 | 22 mm | 22 |
| K- 07 40 20 28 | 18 mm | R 1/2 | 43,0 | 26 mm | 32 |