


K-W90 VERBINDER POM

Union elbows

HANSA FLEX

Caratteristiche

Pressione di lavoro	0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)
Temperatura d'esercizio	-20 °C to +70 °C in air; +1 °C to +70 °C in water
Materiale	Acetalpolymerisat (POM)
Materiale di tenuta	NBR



Nota

Altri dati su richiesta.

Descrizione

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Articolo

Denominazione	per diametro esterno del tubo flessibile Ø mm	L1 (mm)	L2 (mm)
K- 07 40 28 52	4 mm	25,1	25,1
K- 07 40 28 53	5 mm	25,1	25,1
K- 07 40 28 54	6 mm	28,1	28,1
K- 07 40 28 55	8 mm	30,9	30,9
K- 07 40 28 56	10 mm	36,2	36,2
K- 07 40 28 57	12 mm	45,0	45,0
K- 07 40 28 58	15 mm	51,4	51,4
K- 07 40 28 59	18 mm	60,9	60,9
K- 07 40 28 60	22 mm	67,4	67,4
K- 07 40 28 61	28 mm	87,7	87,7