


# K-VERSCHLUSSKAPPEN MS

Hexagonal caps - brass

**HANSA FLEX**

## Caratteristiche

|                        |             |
|------------------------|-------------|
| Pressione di lavoro    | 10 bar      |
| Temperatura del fluido | max. +90 °C |
| Temperatura ambiente   | Max. +90 °C |



## Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Altri dati su richiesta.

## Informazioni supplementari

Further types and dimensions on request.

## Articolo

| Denominazione  | Filetto | L1<br>(mm) | SW    |
|----------------|---------|------------|-------|
| K- 07 40 10 06 | G 1/8   | 10,0       | 13 mm |
| K- 07 40 10 07 | G 1/4   | 10,0       | 16 mm |
| K- 07 40 10 08 | G 3/8   | 10,0       | 19 mm |
| K- 07 40 10 09 | G 1/2   | 12,0       | 23 mm |
| K- 07 40 10 10 | G 3/4   | 14,0       | 29 mm |
| K- 07 40 10 11 | G 1     | 15,0       | 36 mm |
| K- 07 40 10 12 | G 1 1/4 | 17,0       | 46 mm |
| K- 07 40 10 13 | G 1 1/2 | 19,5       | 53 mm |
| K- 07 40 10 14 | G 2     | 19,5       | 64 mm |