
K-PROP VENTIL LU GA 24 V DC

Proportional valves for controlling the flow of air / gas, 24 VDC, closed when de-energised



Caratteristiche			
Campo della temperatura:	Max. 50 °C (G 1/8), Max. 90 °C (G 1/4, G 3/8)		
Mezzi	Air, neutral gases, water, oil		
Intervallo di pressione	Vacuum (max. 8 bar)		
Comando	Via plug amplifier 0 to 10 V, 0 to 20 mA, 4 to 20 mA		
Comportamento Failsafe	Tight closure in case of loss of voltage		
Alloggiamento, sede valvola	Brass		
Parti interne	Stainless steel		
Piatto valvola	FKM		
Materiale di tenuta	FKM		





Nota

Altri dati su richiesta.

Descrizione

Informazioni supplementari

We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000 We recommend combining these proportional valves with a plug amplifier, type K-07250999 or K-07251000

Articolo						
Denominazione	Attacco	DN	differenza di pressione d'esercizio max.	А	В	С
			(bar)	(mm)		(mm)
K- 07 25 09 91	G 1/4	2	8	85,0	40,0 mm	95,0
K- 07 25 09 92	G 1/4	3	4	85,0	40,0 mm	95,0
K- 07 25 09 93	G 3/8	6	1	85,0	48,0 mm	97,0
K- 07 25 09 94	G 3/8	7	1	85,0	48,0 mm	97,0