


Caratteristiche

Pressione d'ingresso	Max. 15 bar
Attacco	G 1/4 internal / external
Materiale	Ottone

**Nota**

Dependent on the input pressure P1, the initial pressure P2 can vary between -20% to +20%

Altri dati su richiesta.

Descrizione

Industry, trade and repair shops often require working pressures of 15 bar or less. These pressure reducing valves, which are screwed directly onto the tool, enable the actually necessary working pressure to be set.
Benefits: Significantly reduced risk of accidents, Longer tool life with fewer malfunctions, Lower noise levels at the workplace.

Articolo

Denominazione	Pressione di regolazione	portata max. (L/min)	A (mm)	B	Ø C (mm)	SW (mm)
K-07 25 19 31	2,0	300	34,0	9,0 mm	17,0	17
K-07 25 02 00	3,0	360	34,0	9,0 mm	17,0	17
K-07 25 02 01	4,0	380	34,0	9,0 mm	17,0	17
K-07 25 02 02	5,0	390	34,0	9,0 mm	17,0	17
K-07 25 02 03	6,0	405	34,0	9,0 mm	17,0	17
K-07 25 19 32	7,0	415	34,0	9,0 mm	17,0	17
K-07 25 19 33	8,0	420	34,0	9,0 mm	17,0	17