

K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

HANSA FLEX

Caratteristiche

Pressione d'ingresso	Min. 2 bar, max. 10 bar
Temperatura del fluido	max. 60 °C
Temperatura ambiente	Max. 60 °C
Collegamento elettrico	Device plug PG 9, type B, EN 175301-803
Grado di protezione	IP 65 (P 54) acc. to DIN 40050
Portata	1600 l/min
Durata d'inserzione relativa	100 %
Attacco per sfiato	Silencer G 1/4
Materiale di tenuta	NBR
Alloggiamento	Die-cast zinc
Misurazione del valore della portata	At P1 = 6 bar and pressure drop $\Delta p = 1$ bar



Nota

If several devices in the »multifix-mini« Series are assembled together, the maximum working pressure is 12 bar. Altri dati su richiesta.

Descrizione

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

Articolo

Denominazione	Filetto	Bobina magnetica	A (mm)	B	C (mm)	Dimensioni strutturali
K- 07 25 11 62	G 1/4	230 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 63	G 1/4	110 V AC, 50 Hz	45,0	29,0 mm	96,0	0
K- 07 25 11 64	G 1/4	24 V DC	45,0	29,0 mm	96,0	0

Parti di ricambio

K-KOPPELPAKET MEHR	Coupling packet
K-GERAETESTECKER	Coupling socket
K-AUTOMAT ABLASSVENTIL	Automatic drain valve
K-MAGNETSPULE MULTIFIX	Solenoid
K-SCHALLDAE SINTERBR SCHLITZ	Silencers, sintered bronze, slotted