

# K-SCHALTVENTILE 3/2 MULTIFIX MINI

On-off valves (3/2-way valves)

**HANSA FLEX**

## Caratteristiche

|   |  |
|---|--|
| <b>Pressione d'ingresso</b>                 | Min. 2 bar, max. 10 bar                            |
| <b>Temperatura del fluido</b>               | max. 60 °C   |
| <b>Temperatura ambiente</b>                 | Max. 60 °C   |
| <b>Collegamento elettrico</b>               | Device plug PG 9, type B, EN 175301-803            |
| <b>Grado di protezione</b>                  | IP 65 (P 54) acc. to DIN 40050                     |
| <b>Portata</b>                              | 1600 l/min   |
| <b>Durata d'inserzione relativa</b>         | 100 %  |
| <b>Attacco per sfiato</b>                   | Silencer G 1/4                                     |
| <b>Materiale di tenuta</b>                  | NBR  |
| <b>Alloggiamento</b>                        | Die-cast zinc                                      |
| <b>Misurazione del valore della portata</b> | At P1 = 6 bar and pressure drop $\Delta p = 1$ bar |



## Nota

If several devices in the »multiflex-mini« Series are assembled together, the maximum working pressure is 12 bar. Altri dati su richiesta.

## Descrizione

Pneumatic systems or parts of systems can be switched on and off by means of an electrical signal. When they are switched off, the system is relieved at the same time.

## Articolo

| Denominazione  | Filetto | Bobina magnetica | A<br>(mm) | B       | C<br>(mm) | Dimensioni strutturali |
|----------------|---------|------------------|-----------|---------|-----------|------------------------|
| K- 07 25 11 62 | G 1/4   | 230 V AC, 50 Hz  | 45,0      | 29,0 mm | 96,0      | 0                      |
| K- 07 25 11 63 | G 1/4   | 110 V AC, 50 Hz  | 45,0      | 29,0 mm | 96,0      | 0                      |
| K- 07 25 11 64 | G 1/4   | 24 V DC          | 45,0      | 29,0 mm | 96,0      | 0                      |

## Parti di ricambio

|                              |                                     |
|------------------------------|-------------------------------------|
| K-KOPPELPAKET MEHR           | Coupling packet                     |
| K-GERAETESTECKER             | Coupling socket                     |
| K-AUTOMAT ABLASSVENTIL       | Automatic drain valve               |
| K-MAGNETSPULE MULTIFIX       | Solenoid                            |
| K-SCHALLDAE SINTERBR SCHLITZ | Silencers, sintered bronze, slotted |