
K-STOPPVENTILE IG

Stop valves, ports 2 and 3 with female thread



Caratteristiche					
Pressione di lavoro	Max. 10 bar				
Pressione di comando	1 - 5 bar, depending on operating pressure				
Temperatura del fluido	max. 70 °C				
Inserzione	Any. Ring pieces can still be rotated 360° after the valve has been tightened				
Materiale	Ottone nichelato				
Materiale di tenuta	Perbunan				





Nota

Altri dati su richiesta.

Descrizione

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Articolo						
Denominazione	Port 1	Port 2	Attacco 3	B (mm)	C (mm)	
K- 07 15 20 46	G 1/8	G 1/8	G 1/8	52,0	21,0	
K- 07 15 20 45	G 1/4	G 1/4	G 1/8	58,0	25,0	
K- 07 15 20 47	G 3/8	G 3/8	G 1/8	63,0	31,0	
K- 07 15 20 44	G 1/2	G 1/2	G 1/8	72,0	40,0	