K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

Caratteristiche

Pressione d'esercizio	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air)
Campo della temperatura:	-10 °C to +60 °C
Portata 6 bar e 10 bar	550 Nl/min
Portata 6 bar e 5 bar	400 Nl/min
Corpo valvola	Alluminio
Molla	Special steel
Pistone	Aluminium
Materiale di tenuta	NBR



Nota

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Altri dati su richiesta.

Informazioni supplementari

Important: The scope of supply does not include a connector. Please order separately.

Articolo

Denominazione	Attacco	Simbolo	Azionamento	Posizioni di commutazione
K- 07 15 00 78	G 1/8	5	monostable	2
K- 07 15 00 79	G 1/8	6	bistabile	2
K- 07 15 00 80	G 1/8	7	monostable	3*
K- 07 15 00 81	G 1/8	8	bistabile	3*

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.