

# K-WV 3/2 MANU PILZTAST

3/2-way pilot valve, manually operated, with mushroom pushbutton, NC

**HANSA FLEX**

## Caratteristiche

|                                 |   |
|---------------------------------|---|
| <b>Pressione d'esercizio</b>    | 2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\nMax. vacuum 10 bar (external pilot air) |
| <b>Campo della temperatura:</b> | -10 °C to +60 °C  |
| <b>Portata 6 bar e 10 bar</b>   | 550 NI/min  |
| <b>Portata 6 bar e 5 bar</b>    | 400 NI/min  |
| <b>Azionamento</b>              | Monostable  |
| <b>Corpo valvola</b>            | Alluminio   |
| <b>Molla</b>                    | Special steel   |
| <b>Pistone</b>                  | Aluminium   |
| <b>Materiale di tenuta</b>      | NBR   |



## Nota

3 valve positions only in conjunction with a second 3/2-way valve. <br>Corresponds to a 5/3-way valve.  
Altri dati su richiesta.

## Informazioni supplementari

Important: The scope of supply does not include a connector. Please order separately.

## Articolo

| Denominazione  | Attacco | Simbolo | Azionamento |
|----------------|---------|---------|-------------|
| K- 07 15 00 86 | G 1/8   | 13      | monostable  |