

# K-WV 5/2 MANU K DREHHEBEL

5/2-way pilot valves, manually operated, with short wing lever

**HANSA FLEX**

## Caratteristiche

<b>Pressione d'esercizio</b>	2.5 - 10 bar (monostabile)\n1.0 - 10 bar (bistabile)\nMax. vacuum 10 bar (external pilot air)
<b>Campo della temperatura:</b>	-10 °C to +60 °C
<b>Portata 6 bar e 10 bar</b>	550 NI/min
<b>Portata 6 bar e 5 bar</b>	400 NI/min
<b>Corpo valvola</b>	Alluminio
<b>Molla</b>	Special steel
<b>Pistone</b>	Aluminium
<b>Materiale di tenuta</b>	NBR



## Nota

\*3 valve positions only in conjunction with a second way valve.

Altri dati su richiesta.

## Informazioni supplementari

Important: The scope of supply does not include a connector. Please order separately.

## Articolo

Denominazione	Attacco	Simbolo	Azionamento	Posizioni di commutazione
K- 07 15 02 37	G 1/8	5	monostabile	2
K- 07 15 02 38	G 1/8	6	bistabile	2
K- 07 15 02 39	G 1/8	7	monostabile	3*
K- 07 15 02 40	G 1/8	8	bistabile	3*