

# K-L-STECK VB 2

Union elbows

**HANSA FLEX**

## Caratteristiche

|                         |                  |
|-------------------------|------------------|
| Pressione di lavoro     | Max. 16 bar      |
| Temperatura d'esercizio | -20 °C to +80 °C |
| Materiale               | Ottone nichelato |
| Anello di compressione  | Hostaform        |
| Anello elastico         | Stainless steel  |



## Nota

Altri dati su richiesta.

## Descrizione

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## Articolo

| Denominazione  | per diametro esterno del tubo flessibile Ø mm | L1<br>(mm) | L2<br>(mm) |
|----------------|---|------------|------------|
| K- 07 40 25 34 | 3 mm  | 10,4       | 10,4       |
| K- 07 40 25 35 | 4 mm  | 16,7       | 16,7       |
| K- 07 40 25 36 | 5 mm  | 19,2       | 19,2       |
| K- 07 40 25 37 | 6 mm  | 19,0       | 19,0       |
| K- 07 40 25 38 | 8 mm  | 21,3       | 21,3       |
| K- 07 40 25 39 | 10 mm   | 23,3       | 23,3       |
| K- 07 40 25 40 | 12 mm   | 26,0       | 26,0       |
| K- 07 40 25 41 | 14 mm   | 29,3       | 29,3       |