


K-VHR 6KT BUND

Hexagon head screw plugs with collar

HANSA FLEX

Caratteristiche

| | |
|------------------------|---|
| Pressione di lavoro | 10 bar |
| Temperatura del fluido | max. +90 °C |
| Temperatura ambiente | Max. +90 °C |
| Tipo | Viti di chiusura a testa esagonale esterna, |
| Materiale | Brass with a bare metal surface |



Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Altri dati su richiesta.

Informazioni supplementari

Further types and dimensions on request.

Articolo

| Denominazione | Filetto | L1 (mm) | L2 (mm) | SW |
|----------------|---------|------------|------------|-------|
| K- 07 40 44 47 | G 1/8 | 17,0 | 8,0 | 10 mm |
| K- 07 40 44 49 | G 1/4 | 21,0 | 12,0 | 13 mm |
| K- 07 40 44 51 | G 3/8 | 21,0 | 12,0 | 17 mm |
| K- 07 40 44 53 | G 1/2 | 26,0 | 14,0 | 19 mm |
| K- 07 40 44 55 | G 3/4 | 30,0 | 16,0 | 24 mm |
| K- 07 40 44 57 | G 1 | 32,0 | 16,0 | 27 mm |