

K-VT 2 KUPPL 7,2 STECKNIP MS

Distributors with 2 quick disconnect couplings DN 7.2, brass with push in plug DN 7.2 - DN 7.8

HANSA FLEX

Caratteristiche

Pressione d'esercizio	0 - 35 bar
Temperatura del fluido	-20 °C to +100 °C
Alloggiamento	Brass
Fusibile e guarnizione	Industrial glue, mid hardened



Nota

Couplings and distributors are also available separately
Altri dati su richiesta.

Descrizione

1, 2 or 3-way distributor pieces made of brass, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Informazioni supplementari

Couplings and distributors are also available separately

Articolo

Denominazione	Attacco	Giunto di accoppiamento	composto da distributore
K- 07 40 40 48	Plugs DN 7.2 to 7.8 / G 3/8	K-07350025	K-07404016
K- 07 40 44 27	Plugs DN 7.2 to 7.8 / G 1/2	K-07350026	K-07404017

è un accessorio dei seguenti prodotti

K-VSEH 3-KRAFT	Receptacle combinations »3-Kraft«
K-VSEH AIRKRAFT	Receptacle combinations »airkraft«