

K-VENTILSCHEIBE HDM 6

Valve discs for HDM valve terminal with 6 mm port

HANSA FLEX

Caratteristiche

| | |
|---------------------------------------|---|
| Mezzi | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Pressione di lavoro | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Pressione di comando | 3 - 7 bar |
| Campo della temperatura: | -10 °C to +60 °C |
| Portata | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Numero di comandi | Max. 16 (e.g. 16 spring return valves) |
| Azionamento ausiliario manuale | Latching (bistable), Monostable (non-latching) version also available on request |
| Potenza assorbita | 0.6 W per pilot |
| Grado di protezione | IP 65 |



Nota

Altri dati su richiesta.

Descrizione

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Informazioni supplementari

Important: The scope of supply does not include a connector. Please order separately.

Articolo

| Denominazione | Funzione |
|----------------|--|
| K- 07 15 20 60 | 2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted |
| K- 07 15 20 67 | 2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised |
| K- 07 15 20 62 | 3/2-way, NC, monostable and 3/2-way, NO, monostable |
| K- 07 15 20 66 | 5/2-way, monostable |
| K- 07 15 20 59 | 5/2-way, monostable (uses only one pin, two signals assigned) |
| K- 07 15 20 61 | 5/2-way, bistable (pulse valve) |
| K- 07 15 20 64 | 5/3-way, mid-position closed |