

# K-LP ALU O DUESE

Blow guns die-cast aluminium nickel-plated, without nozzle, Safety

**HANSA FLEX**

## Caratteristiche

|                         |                  |
|-------------------------|------------------|
| Pressione d'esercizio   | max. 10 bar      |
| Temperatura d'esercizio | -10 °C to +50 °C |
| Ugelli e prolunghhe     | Thread M12x1.25  |



## Nota

Altri dati su richiesta.

## Descrizione

Standard type without nozzle! In combination with the safety nozzles described below, this blow gun meets a wide range of safety requirements. For blowing out and cleaning machines, workpieces, bore holes, hollow parts, etc.

## Articolo

| Denominazione  | Attacco                                | Filetto dell'attacco |
|----------------|--|----------------------|
| K- 07 10 00 07 | Stem, I.D. 6                           | G 1/4                |
| K- 07 10 00 10 | Stem, I.D. 9                           | G 1/4                |
| K- 07 10 00 14 | Stem, I.D. 13                          | G 1/4                |
| K- 07 10 00 18 | connection nipples for coupling NW 7,2 | G 1/4                |

## Accessori

|                             |  |
|-----------------------------|--|
| K-ZUBEH LP ALU              | Accessories for standard blow guns (series 22)     |
| K-FEINSTRALHDUE LAERMARME M | Low-noise fine-spray nozzles, M12x1.25 connection  |
| K-RUNDDUESE LAERMARME M     | Low-noise round nozzles, M12x1.25 connection       |
| K-FLACHDUESE LAERMARME M    | Low-noise flat nozzles, M12x1.25 connection        |
| K-STANDARDUESE              | Standard nozzle (short version) with Ø 1.5 mm bore |
| K-DAEMPFERDUESE             | Silencer nozzle, M12x1.25 connection               |
| K-DUESE MIT SCHUTZSCHILD    | Nozzle with chip shield, M12x1.25 connection       |
| K-VERL DUESE                | Extension nozzles                                  |
| K-DRUCKREGULIERDUESE        | Regulating nozzle, M12x1,25, Safety                |