# K-FLACHDUESE LAERMARME

Low-noise flat nozzles



## Nota

For noise, air consumption and blowing force values, see diagrams 1-17 in the technical information.

## Descrizione

If correctly designed, these noise-reducing nozzles guarantee a lower noise level than conventional one-hole types with an identical blowing force. They are usually fitted with a noise-reducing plastic insert and they are recommended by the German BGIA (Institute for Occupational Safety and Health).

## Articolo

| Denominazione | Larghezza ugello (mm) | Filetto | Lunghezza (mm) | Materiale | Diagramma |
|---|---|---|---|---|---|
| **K- 07 10 09 60** | 21,5 | G 1/4 male | 100,0 | Nickel-plated brass | 11 |
| **K- 07 10 09 61** | 29,0 | G 3/8 male | 100,0 | Nickel-plated brass | 12 |
| **K- 07 10 09 62** | 16,5 | G 3/8 male | 50,0 | Galvanised steel | 14 |
| **K- 07 10 09 63** | 21,0 | G 1/4 male | 100,0 | Nickel-plated brass | 13 |
| **K- 07 10 09 64** | 29,0 | G 3/8 male | 100,0 | Nickel-plated brass | 15 |

*Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.*