

# K-EINGANGSPL VENTILINSEL HDM

Input plates for HDM valve terminal

**HANSA FLEX**

## Caratteristiche

|                                       |   |
|---------------------------------------|---|
| <b>Mezzi</b>                          | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| <b>Pressione di lavoro</b>            | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)                      |
| <b>Pressione di comando</b>           | 3 - 7 bar   |
| <b>Campo della temperatura:</b>       | -10 °C to +60 °C  |
| <b>Portata</b>                        | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)  |
| <b>Numero di comandi</b>              | Max. 16 (e.g. 16 spring return valves)  |
| <b>Azionamento ausiliario manuale</b> | Latching (bistable), Monostable (non-latching) version also available on request                    |
| <b>Potenza assorbita</b>              | 0.6 W per pilot   |
| <b>Grado di protezione</b>            | IP 65   |



## Nota

Altri dati su richiesta.

## Descrizione

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Informazioni supplementari

Important: The scope of supply does not include a connector. Please order separately.

## Articolo

| Denominazione  | Funzione                     | Attacco                     |
|----------------|------------------------------|-----------------------------|
| K- 07 15 22 49 | Standard, internal pilots    | Multi-pole                  |
| K- 07 15 22 48 | External pilots, dual supply | Multi-pole                  |
| K- 07 15 22 54 | Standard, internal pilots    | With integrated Profibus DP |
| K- 07 15 22 53 | External pilots              | With integrated Profibus DP |