# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges, CrNi steel type

## Caratteristiche

| | |
|---|---|
| **Tipo** | 233.50 |
| **Esecuzione** | Glycerine-filled bourdon-tube pressure gauge, CrNi steel type |
| **Applicazione** | For gaseous or liquid, corrosive and crystallising mediawhich do not have high viscosity, also in corrosive atmosphere |
| **Classe di qualità** | 1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm) |
| **Temperatura del fluido** | max. +100 °C |
| **Temperatura ambiente** | da -20 °C a +60 °C |
| **Alloggiamento** | CrNi steel |
| **Oculare** | Laminated safety glass Ø 63 = Polycarbonate |




## Nota

Altri dati su richiesta.

## Descrizione

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

## Articolo

| Denominazione | Campo di misurazione | Ø (mm) | Attacco |
|---|---|---|---|
| **K- 07 20 11 93** | -1 / 0.0 bar | 63,0 | G 1/4" |
| **K- 07 20 11 95** | -1 / +0.6 bar | 63,0 | G 1/4" |
| **K- 07 20 11 97** | -1 / +1.5 bar | 63,0 | G 1/4" |
| **K- 07 20 11 99** | -1 / +3.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 01** | -1 / +5.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 03** | -1 / +9.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 05** | -1 / +15.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 08** | 0 - 1.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 10** | 0 - 1.6 bar | 63,0 | G 1/4" |
| **K- 07 20 12 12** | 0 - 2.5 bar | 63,0 | G 1/4" |
| **K- 07 20 12 14** | 0 - 4.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 16** | 0 - 6.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 18** | 0 - 10.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 20** | 0 - 16.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 22** | 0 - 25.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 24** | 0 - 40.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 26** | 0 - 60.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 28** | 0 - 100.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 30** | 0 - 160.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 32** | 0 - 250.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 34** | 0 - 400.0 bar | 63,0 | G 1/4" |
| **K- 07 20 12 36** | 0 - 600.0 bar | 63,0 | G 1/4" |
| **K- 07 20 11 92** | -1 / 0.0 bar | 100,0 | G 1/2" |
| **K- 07 20 11 94** | -1 / +0.6 bar | 100,0 | G 1/2" |
| **K- 07 20 11 96** | -1 / +1.5 bar | 100,0 | G 1/2" |
| **K- 07 20 11 98** | -1 / +3.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 00** | -1 / +5.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 02** | -1 / +9.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 04** | -1 / +15.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 06** | 0 - 0.6 bar | 100,0 | G 1/2" |
| **K- 07 20 12 07** | 0 - 1.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 09** | 0 - 1.6 bar | 100,0 | G 1/2" |
| **K- 07 20 12 11** | 0 - 2.5 bar | 100,0 | G 1/2" |
| **K- 07 20 12 13** | 0 - 4.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 15** | 0 - 6.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 17** | 0 - 10.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 19** | 0 - 16.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 21** | 0 - 25.0 bar | 100,0 | G 1/2" |

*Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.*

# K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges, CrNi steel type

HANSA-FLEX

## Articolo

| Denominazione | Campo di misurazione | Ø (mm) | Attacco |
|---|---|---|---|
| **K- 07 20 12 23** | 0 - 40.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 25** | 0 - 60.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 27** | 0 - 100.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 29** | 0 - 160.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 31** | 0 - 250.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 33** | 0 - 400.0 bar | 100,0 | G 1/2" |
| **K- 07 20 12 35** | 0 - 600.0 bar | 100,0 | G 1/2" |
| **K- 07 20 03 48** | 0 - 0.6 bar | 160,0 | G 1/2" |
| **K- 07 20 03 49** | 0 - 1.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 50** | 0 - 1.6 bar | 160,0 | G 1/2" |
| **K- 07 20 03 51** | 0 - 2.5 bar | 160,0 | G 1/2" |
| **K- 07 20 03 52** | 0 - 4.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 53** | 0 - 6.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 54** | 0 - 10.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 55** | 0 - 16.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 56** | 0 - 25.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 57** | 0 - 40.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 58** | 0 - 60.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 59** | 0 - 100.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 60** | 0 - 160.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 61** | 0 - 250.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 62** | 0 - 400.0 bar | 160,0 | G 1/2" |
| **K- 07 20 03 63** | 0 - 600.0 bar | 160,0 | G 1/2" |

*Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.*