

K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,
CrNi steel type

HANSA FLEX

Caratteristiche

Tipo	233.50
Esecuzione	Glycerine-filled bourdon-tube pressure gauge, CrNi steel type
Applicazione	For gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere
Classe di qualità	1.6 (Ø 63 mm), 1.0 (Ø 100 mm and Ø 160 mm)
Temperatura del fluido	max. +100 °C
Temperatura ambiente	da -20 °C a +60 °C
Alloggiamento	CrNi steel
Oculare	Laminated safety glass Ø 63 = Polycarbonate



Nota

Altri dati su richiesta.

Descrizione

For use in the chemical/petrochemical process industry, power stations, machinery and industrial plant engineering. For measuring points with high dynamic pressure loads and vibrations.

Articolo

Denominazione	Campo di misurazione	Ø (mm)	Attacco
K- 07 20 11 93	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 11 95	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 11 97	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 11 99	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 12 01	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 12 03	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 12 05	-1 / +15.0 bar	63,0	G 1/4"
K- 07 20 12 08	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 12 10	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 12 12	0 - 2.5 bar	63,0	G 1/4"
K- 07 20 12 14	0 - 4.0 bar	63,0	G 1/4"
K- 07 20 12 16	0 - 6.0 bar	63,0	G 1/4"
K- 07 20 12 18	0 - 10.0 bar	63,0	G 1/4"
K- 07 20 12 20	0 - 16.0 bar	63,0	G 1/4"
K- 07 20 12 22	0 - 25.0 bar	63,0	G 1/4"
K- 07 20 12 24	0 - 40.0 bar	63,0	G 1/4"
K- 07 20 12 26	0 - 60.0 bar	63,0	G 1/4"
K- 07 20 12 28	0 - 100.0 bar	63,0	G 1/4"
K- 07 20 12 30	0 - 160.0 bar	63,0	G 1/4"
K- 07 20 12 32	0 - 250.0 bar	63,0	G 1/4"
K- 07 20 12 34	0 - 400.0 bar	63,0	G 1/4"
K- 07 20 12 36	0 - 600.0 bar	63,0	G 1/4"
K- 07 20 11 92	-1 / 0.0 bar	100,0	G 1/2"
K- 07 20 11 94	-1 / +0.6 bar	100,0	G 1/2"
K- 07 20 11 96	-1 / +1.5 bar	100,0	G 1/2"
K- 07 20 11 98	-1 / +3.0 bar	100,0	G 1/2"
K- 07 20 12 00	-1 / +5.0 bar	100,0	G 1/2"
K- 07 20 12 02	-1 / +9.0 bar	100,0	G 1/2"
K- 07 20 12 04	-1 / +15.0 bar	100,0	G 1/2"
K- 07 20 12 06	0 - 0.6 bar	100,0	G 1/2"
K- 07 20 12 07	0 - 1.0 bar	100,0	G 1/2"
K- 07 20 12 09	0 - 1.6 bar	100,0	G 1/2"
K- 07 20 12 11	0 - 2.5 bar	100,0	G 1/2"
K- 07 20 12 13	0 - 4.0 bar	100,0	G 1/2"
K- 07 20 12 15	0 - 6.0 bar	100,0	G 1/2"
K- 07 20 12 17	0 - 10.0 bar	100,0	G 1/2"
K- 07 20 12 19	0 - 16.0 bar	100,0	G 1/2"
K- 07 20 12 21	0 - 25.0 bar	100,0	G 1/2"



Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.

10.04.2026

HANSA-FLEX AG

www.hansa-flex.com

K-GMM 1

Glycerine-filled pressure gauges Glycerine-filled pressure gauges,
CrNi steel type

HANSA FLEX

Articolo

Denominazione	Campo di misurazione	Ø (mm)	Attacco
K- 07 20 12 23	0 - 40.0 bar	100,0	G 1/2"
K- 07 20 12 25	0 - 60.0 bar	100,0	G 1/2"
K- 07 20 12 27	0 - 100.0 bar	100,0	G 1/2"
K- 07 20 12 29	0 - 160.0 bar	100,0	G 1/2"
K- 07 20 12 31	0 - 250.0 bar	100,0	G 1/2"
K- 07 20 12 33	0 - 400.0 bar	100,0	G 1/2"
K- 07 20 12 35	0 - 600.0 bar	100,0	G 1/2"
K- 07 20 03 48	0 - 0.6 bar	160,0	G 1/2"
K- 07 20 03 49	0 - 1.0 bar	160,0	G 1/2"
K- 07 20 03 50	0 - 1.6 bar	160,0	G 1/2"
K- 07 20 03 51	0 - 2.5 bar	160,0	G 1/2"
K- 07 20 03 52	0 - 4.0 bar	160,0	G 1/2"
K- 07 20 03 53	0 - 6.0 bar	160,0	G 1/2"
K- 07 20 03 54	0 - 10.0 bar	160,0	G 1/2"
K- 07 20 03 55	0 - 16.0 bar	160,0	G 1/2"
K- 07 20 03 56	0 - 25.0 bar	160,0	G 1/2"
K- 07 20 03 57	0 - 40.0 bar	160,0	G 1/2"
K- 07 20 03 58	0 - 60.0 bar	160,0	G 1/2"
K- 07 20 03 59	0 - 100.0 bar	160,0	G 1/2"
K- 07 20 03 60	0 - 160.0 bar	160,0	G 1/2"
K- 07 20 03 61	0 - 250.0 bar	160,0	G 1/2"
K- 07 20 03 62	0 - 400.0 bar	160,0	G 1/2"
K- 07 20 03 63	0 - 600.0 bar	160,0	G 1/2"