

# K-SCHLAUCH KUPPLUNG SET STAN

Hose and coupling kits, with straight hose and DN 7.6 standard coupling

**HANSA FLEX**

## Caratteristiche

|                        |                  |
|------------------------|------------------|
| Pressione d'esercizio  | 16 bar           |
| Temperatura del fluido | -20 °C to +60 °C |



## Nota

Altri dati su richiesta.

## Descrizione

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Articolo

| Denominazione  | Dimensione tubo flessibile | Lunghezza di lavoro (m) |
|----------------|----------------------------|-------------------------|
| K- 07 10 05 62 | 12 mm x 8 mm               | 10,0                    |
| K- 07 10 05 63 | 12 mm x 8 mm               | 15,0                    |
| K- 07 10 05 64 | 16 mm x 11 mm              | 10,0                    |
| K- 07 10 05 65 | 16 mm x 11 mm              | 15,0                    |