

# K-VLST L AG IG MS NI

Extensions, long, parallel - nickel-plated brass

## Caratteristiche

|                         |                  |
|-------------------------|------------------|
| Temperatura d'esercizio | Max. 150 °C      |
| Pressione               | Max. 60 bar      |
| Materiale               | Ottone nichelato |



## Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.  
Altri dati su richiesta.

## Descrizione

Suitable for air, water, oil, steam, etc.

## Informazioni supplementari

Further types and dimensions on request.

## Articolo

| Denominazione  | Filettatura esterna | Filettatura interna | L1<br>(mm) | SW    |
|----------------|---------------------|---------------------|------------|-------|
| K- 07 40 39 16 | G 1/8               | G 1/8               | 22,0       | 14 mm |
| K- 07 40 39 17 | G 1/8               | G 1/8               | 42,0       | 14 mm |
| K- 07 40 39 18 | G 1/8               | G 1/8               | 51,0       | 14 mm |
| K- 07 40 39 19 | G 1/8               | G 1/8               | 100,0      | 14 mm |
| K- 07 40 39 20 | G 1/4               | G 1/4               | 35,0       | 17 mm |
| K- 07 40 39 21 | G 1/4               | G 1/4               | 51,0       | 17 mm |
| K- 07 40 39 22 | G 1/4               | G 1/4               | 100,0      | 17 mm |