
K-VLST L AG IG MS NI

Extensions, long, parallel - nickel-plated brass

Caratteristiche

Temperatura d'esercizio	Max. 150 °C
Pressione	Max. 60 bar
Materiale	Ottone nichelato





Nota

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes.
Altri dati su richiesta.

Descrizione

Suitable for air, water, oil, steam, etc.

Informazioni supplementari

Further types and dimensions on request.

Articolo

Denominazione	Filettatura esterna	Filettatura interna	L1 (mm)	SW
K- 07 40 39 16	G 1/8	G 1/8	22,0	14 mm
K- 07 40 39 17	G 1/8	G 1/8	42,0	14 mm
K- 07 40 39 18	G 1/8	G 1/8	51,0	14 mm
K- 07 40 39 19	G 1/8	G 1/8	100,0	14 mm
K- 07 40 39 20	G 1/4	G 1/4	35,0	17 mm
K- 07 40 39 21	G 1/4	G 1/4	51,0	17 mm
K- 07 40 39 22	G 1/4	G 1/4	100,0	17 mm

Nonostante il più attento esame non si possono escludere eventuali errori ed omissioni, non ci assumiamo alcuna responsabilità per le indicazioni contenute.