



# K-BKR ROT STAHLHEBEL IG AG

Ball valves with red steel lever, lightweight type, female/male thread

**HANSA FLEX**

## Caratteristiche

<b>Campo di impiego</b>	Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture
<b>Pressione d'esercizio</b>	Max. 40 bar
<b>Temperatura d'esercizio</b>	-15 °C to +90 °C
<b>Filettatura descrizione</b>	G thread acc. DIN EN ISO 228-1
<b>Alloggiamento</b>	Nickel-plated brass
<b>Leva</b>	Steel, with plastic coating
<b>Sfera</b>	Chrome-plated brass
<b>Guarnizione sfera</b>	PTFE
<b>Guarnizione mandrino</b>	HNBR / EPDM / PTFE. 2 O-Rings (HNBR / EPDM) 1 gasket (PTFE) additional PTFE-gasket



## Nota

Altri dati su richiesta.

## Articolo

Denominazione	DN	Filetto	A (mm)	B (mm)	L (mm)
K- 07 30 00 50	8	G 1/4	85,0	42,0	44,0
K- 07 30 00 54	10	G 3/8	85,0	42,0	51,0
K- 07 30 00 58	15	G 1/2	85,0	46,0	60,0
K- 07 30 00 62	20	G 3/4	105,0	53,0	70,0
K- 07 30 00 66	25	G 1	105,0	57,0	79,0
K- 07 30 00 70	32	G 1 1/4	130,0	70,0	91,0
K- 07 30 00 74	40	G 1 1/2	130,0	76,0	104,0
K- 07 30 00 78	50	G 2	165,0	92,0	122,0