

K-SVKM NW 7,2 AG VA

Quick disconnect couplings DN 7.2, stainless steel, male

HANSA FLEX

Caratteristiche

| | |
|---------------------------------------|---|
| Pressione d'esercizio | 1 - 35 bar and rough vacuum |
| Portata aria | 1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| Temperatura del fluido | -25 °C to +200 °C |
| Alloggiamento, bussola, corpo valvola | Stainless steel 1.4305 |
| Molla, anello elastico | Stainless steel 1.4310 |
| Perni di bloccaggio | Stainless steel 1.4401 |
| Materiale di tenuta | FKM |



Nota

Altri dati su richiesta.

Descrizione

Classic standard coupling type, one side sealing, made of stainless steel. The closed sleeve protects the coupling from dirt. We recommend the use of stainless steel plugs and stems!

Articolo

| Denominazione | Attacco | Lunghezza (mm) | SW (mm) |
|----------------|------------|----------------|---------|
| K- 07 35 07 59 | G 1/4 male | 43,0 | 22 |
| K- 07 35 07 60 | G 3/8 male | 43,0 | 22 |
| K- 07 35 07 61 | G 1/2 male | 46,0 | 24 |

Elementi supplementari

| | |
|----------------------------|---|
| K-NIPPEL KUPPL NW7 AG VA 2 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male |
| K-NIPPEL KUPPL NW7 IG VA 1 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female |
| K-TUE 7,2 7,8 VA 2 | Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305 |